

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
14 July 2005 (14.07.2005)

PCT

(10) International Publication Number
WO 2005/064997 A1

(51) International Patent Classification⁷: **H05B 41/288**

(21) International Application Number:
PCT/JP2004/019697

(22) International Filing Date:
22 December 2004 (22.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-433532 26 December 2003 (26.12.2003) JP

(71) Applicant (for all designated States except US): **MAT-SUSHITA ELECTRIC WORKS, LTD.** [JP/JP]; 1048, Oaza-Kadoma, Kadoma-shi, Osaka 5718686 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SUGANUMA, Kazutoshi** [JP/JP]; c/o Matsushita Electric Works, Ltd., 1048, Oaza-Kadoma, Kadoma-shi, Osaka 5718686 (JP). **KANBARA, Takashi** [JP/JP]; c/o Matsushita Electric Works, Ltd., 1048, Oaza-Kadoma, Kadoma-shi, Osaka 5718686 (JP). **TANAKA, Toshifumi** [JP/JP]; c/o Matsushita Electric Works, Ltd., 1048, Oaza-Kadoma, Kadoma-shi, Osaka 5718686 (JP).

(74) Agents: **KAWAMIYA, Osamu et al.**; Aoyama & Partners, IMP Building, 3-7, Shiromi 1-chome, Chuo-ku, Osaka-shi, Osaka 5400001 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: DISCHARGE LAMP LIGHTING APPARATUS AND LAMP SYSTEM USING THE LIGHTING APPARATUS



(57) Abstract: In a discharge lamp lighting apparatus, a power supplied to a discharge lamp La through a DC-DC converter 1 and an inverter 2 is controlled depending on detection results of a lamp voltage detection unit 6 and a lamp current detection unit 7, and in an electrode heating period an alternation time of an output to the discharge lamp when starting actuation of the discharge lamp is set longer than an alternation time in a steady lighting period, and the alternation time in the electrode heating period is increased depending on lowering of a supply power or current to the discharge lamp. Thus, even when a lamp current is suddenly changed, the discharge lamp is prevented from going off at the time of polarity inversion without lowering a life.

WO 2005/064997 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.